

Clogged Bathroom Sink

If your bathroom sink drains slowly, it's most likely due to buildup in the trap. Fortunately, this is easy to fix—usually with just a rubber plunger.

Hair, soap residue, and grime often accumulate in the trap (the white plastic part under the sink), forming a clog that blocks the water. A plunger usually takes care of it:

1. Cover the overflow hole with your thumb or some tape.
2. Place the plunger over the drain and fill the sink halfway with water.
3. Plunge up and down firmly. The suction usually dislodges the clog.

If the plunger doesn't work, you can unscrew the bottom part of the trap by hand (do not use tools).

- Place a bucket underneath to catch any dirty water.
- Use your finger or a screwdriver to remove visible debris.
- Make sure nothing is left behind, then reattach the trap and check for leaks.

If it still doesn't work and the sink is blocked, please contact ByggVesta and make a service request.

A plunger is a useful tool

A plunger is inexpensive, effective, and worth having at home for situations like this.



1. Cover the overflow hole with your thumb or some tape. Place the plunger over the drain and fill the sink halfway with water. Plunge up and down firmly. The suction usually dislodges the clog.



2. If the plunger doesn't work: Place a bucket underneath to catch any dirty water, and open the trap (see 3.).



3. If the plunger doesn't work, you can unscrew the bottom part of the trap by hand (do not use tools).



4. Use your finger or a screwdriver to remove visible debris. Make sure nothing is left behind, then reattach the trap (by hand, do not use any tools), and check for leaks.